19 Inch 3U Outdoor Telecom Cabinets Weatherproof Data Cabinet With **Energy Backup System**

Basic Information

• Place of Origin: **SHENZHEN**

• Brand Name: daxin CE · Certification:

• Model Number: ODC-210909C2T-200AH

• Minimum Order

· Packaging Details:

Quantity:

Woodcase/ Paper box

1 pcs

• Delivery Time: 15-25 days

• Payment Terms: T/T

• Supply Ability: 10000pcs/month



Product Specification

· Features: Commercial Power Safe, Industrial

Commercial Storage, Commercial Energy

Backup

• Other Accessory: Sensor

· Cabinet Layout: One Compartment

Jacket OD: 3.0mm

• Energy Storage System Industrial And Commercial

Type:

· Battery Shelf: One

 Cabinet Lock: Anti-theft Three Point Lock

• Highlight: Weatherproof 3U Outdoor Telecom Cabinets,

> 19 Inch Outdoor Weatherproof Data Cabinet, 19 Inch 3U Weatherproof Data Cabinet

Product Description:

One of the key features of these cabinets is their anti-theft three-point lock system, which ensures that the equipment stored inside is safe and secure. This lock system is designed to prevent unauthorized access to the cabinet, making it an ideal choice for outdoor wireless cabinet, outdoor mobile cabinet, and outdoor network cabinet applications.

The Outdoor Telecom Cabinets are also designed with a jacket OD of 3.0mm, which provides additional protection against weather elements such as rain, snow, and wind. This makes the cabinets ideal for use in areas where extreme weather conditions are common. Another key feature of these cabinets is their commercial power safe design, which provides safe and reliable power to the equipment stored inside. This feature is particularly important for applications in the telecommunications industry, where uninterrupted power supply is essential for the smooth operation of critical equipment.

The Outdoor Telecom Cabinets also feature industrial commercial storage, which provides ample storage space for telecommunication equipment. This storage space is designed to accommodate a wide range of equipment, including servers, routers, and other network equipment.

Additionally, these cabinets are equipped with a commercial energy backup system, which provides a reliable source of backup power in the event of a power outage. This feature is particularly important for applications in the renewable energy industry, where reliable backup power is essential for the smooth operation of equipment.

The energy storage system type used in these cabinets is industrial and commercial, which makes them ideal for a wide range of applications. This energy storage system is designed to provide reliable and efficient power to the equipment stored inside, ensuring that it operates smoothly and efficiently at all times.

In summary, the Outdoor Telecom Cabinets are a reliable and secure storage solution for telecommunication equipment. With their anti-theft three-point lock system, jacket OD of 3.0mm, commercial power safe design, industrial commercial storage, commercial energy backup system, and industrial and commercial energy storage system type, these cabinets are ideal for a wide range of applications in the telecommunications, transportation, renewable energy, and outdoor events industries.

Features:

Product Name: Outdoor Telecom Cabinets

Certification: CE

Cabinet Lock: Anti-theft Three Point Lock
Surface Coating: Outdoor Powder Coating

Features:

Commercial Power Safe Industrial Commercial Storage Commercial Energy Backup

Applications:

Telecommunications

Transportation

Renewable Energy

Outdoor Events

Technical Parameters:

Product Attribute	Value	
Product Name	Outdoor Telecommunication Locker	
Manufacturer	Shenzhen	
Certification	CE	
Surface Coating	Outdoor Powder Coating	
Price	6000 USD	
Cabinet Lock	Anti-theft Three Point Lock	
Battery Shelf	One	
Delivery Time	30 days	
Other Accessory	Sensor	
Supply Ability	10,000 Taiwan/month	

Applications:

This outdoor wireless cabinet is perfect for outdoor applications and scenarios such as:

Telecom base stations

Wireless communication

Outdoor power cabinets

Outdoor cooling cabinets

The ODC-210909C2T-200AH is designed to withstand extreme weather conditions and harsh environments. It is made of high-quality materials that are resistant to corrosion, rust, and erosion. This product is also equipped with a cooling system that has a cooling capacity of 500W, making it ideal for outdoor cooling cabinets.

The energy storage system type of this outdoor wireless cabinet is industrial and commercial, making it suitable for various applications that require high energy storage. The jacket OD of this product is 3.0mm, providing extra protection and durability.

If you are looking for an outdoor telecom enclosure that can withstand harsh environments and extreme weather conditions, the daxin ODC-210909C2T-200AH Outdoor Telecom Cabinet is the perfect choice. The minimum order quantity of this product is 10, and it is priced at 6000USD. Our payment term is T/T, and we have a supply ability of 10,000 Taiwan/month. The delivery time for this product is 30 days, and it is packaged in a wooden crate/cardboard box for safe transportation.

Support and Services:

Our Outdoor Telecom Cabinets are designed to withstand harsh environments and provide reliable protection for your telecommunications equipment. Our technical support team is available to assist with any product-related questions or issues you may encounter

We also offer a range of services to ensure that your cabinets are properly installed and maintained, including site surveys, installation support, and preventative maintenance programs. Our team of experienced technicians will work with you to develop a customized solution that meets your specific needs and requirements.

Additionally, we offer training programs to help your staff understand the capabilities and features of our cabinets, as well as best practices for maintenance and troubleshooting.

Packing and Shipping:

Product Packaging:

The outdoor telecom cabinet will be packaged in a sturdy cardboard box with protective foam padding to ensure safe transportation. The cabinet components will be securely wrapped and separated to avoid any damage during transit.

The outdoor telecom cabinet will be shipped via a reputable courier service and will require a signature upon delivery. Shipping costs will be calculated based on the destination and weight of the package. Estimated delivery times will be provided upon checkout and may vary depending on the location.

FAQ:

Q1: What is the brand name of this Outdoor Telecom Cabinet?

A1: The brand name of this Outdoor Telecom Cabinet is daxin.

Q2: What is the model number of this Outdoor Telecom Cabinet?

A2: The model number of this Outdoor Telecom Cabinet is ODC-210909C2T-200AH.

Q3: Is this Outdoor Telecom Cabinet CE certified?
A3: Yes, this Outdoor Telecom Cabinet is CE certified.

Q4: Where is this Outdoor Telecom Cabinet made?

A4: This Outdoor Telecom Cabinet is made in SHENZHEN.

Q5: What is the minimum order quantity for this Outdoor Telecom Cabinet?

A5: The minimum order quantity for this Outdoor Telecom Cabinet is 10 units.

Price: 6000USD
Payment Terms: T/T

Supply Ability: 10000Taiwan/month

Delivery Time: 30 days

Packaging Details: Wooden crate/cardboard box



Product list			
Number	Name/Description	Specification/Model	Parameter
1	Outdoor integrated power cabinet	900°900°2150	A. Cabinet dimensions: W × DxH900 * 900 * 2150mm; Internal dimensions: W × DxH800 * 800 * 1800mm B. Cabinet composition: cabinet body+cabinet door+base+top cover+rack+battery layer board+cabinet lock C. Cabinet type: 1 unit, 1 compartment, front door, floor mounted D. Cabinet material: 1.5mm galvanized sheet; E. Thermal insulation performance: thermal conductivity<0.472W/(mz. k); F. Upper equipment rack: 19 inch rack, 22U, 3 pairs of support bars, 1 pallet; The lower two battery racks can accommodate up to 2 sets of 48200AH lead-acid batteries; G. Cabinet base: 100mm high, 2.0mm thick; H. Entry method: Bottom in and bottom out with a diameter of 50 * 4; L. Anti theft design: embedded doors, embedded links, point type anti-theft locks; J. Protection level: IP65; K. Color: RAL7035, professional outdoor powder coating; L. Screen printing of cabinet with "Danger of Electricity" label; M. Including grounding copper bar, LED light, door magnetic switch, and cooling fan (optional)
2	Embedded switch power supply 200A	ET-PS48200Z-6U	Standard 19 inches, embedded plug-in frame 3U high; AC input 220V, DC output 48V; Equipped with 3 30A rectifier modules and 1 monitoring and management module; Capable of battery charging management; Distribution section: AC input: air switch D247-63/2P C63 63A/2P * 1; Three phase AC C-level lightning arrester 20-40KA; Communication output: Air switch D247-63/2 C32 32A/2P * 1; Ground wire terminal * 1; DC C-level lightning arrester 20-40KA 1P * 1; DC output: One power outage: D247-63/1 C63 63A/1P * 3; Secondary power off: D247-63/1 C63 63A/1P * 3:
3	Distribution unit (optional/customizable)	3U	19 inch 3U high embedded plug-in frame, AC380V input, $63A/4P \times 2$ (AC input, oil engine input-mechanical interlock plate), three-phase B-class lightning arrester $\times 1$, $63A/3P \times 1$, $32A/1P \times 2$, $16A/1P \times 2$, $10A/1P \times 1$, $6A/1P \times 1$, three hole maintenance socket $\times 1$, ground row $\times 1$, zero row $\times 1$.
4	Lithium battery/lead- acid battery (optional)	3u 100AH	48V 100AH
5	FSU	10	8 RS485 serial ports, 8 DI inputs, 4 DO dry contact outputs, 1 mains power status detection input, 1 water immersion detection input, 1 built-in vibration sensor, 1 USB interface, 1 R345 IP port, 1 consolo debugging port, port lightning and surge protection. The software comes with a web management interface, which allows for the configuration of the collector through a web browser, as well as the viewing of real-time collected data, alarms, and controls. Historical data and alarms can also be queried; Support centralized monitoring through SNMP or 8 interface access to the backend monitoring system.
6	Camera	2 million infrared hemisphere	
7	UPS	3KVA	
8	Communication air conditioning	1500W	AC 220V



Main equipment for cabinet processing (Three main equipment)







TRUMATIC500- Fully Automatic



TRUMATIC500- Fully Automatic Japan AMADA - Fully Automatic

1500W: 1tower 3000W: 2tower > Fast data punching: 4 u nits with automatic loading and unloading

➤ Japan AMADA: 7 units wi th automatic loading and unloading ➤ Model: EM-2510NT/AC-25 10NT

Key process - general punching, ben ding, and riveting workshop



Model: RG-35S



> TOX riveting m



Puchong: 5 units (160T+250T+300T)



Key Process - Copper and Aluminum Product Workshop (Integrat ed Cutting and Punching Machine)



- > Copper bar integrated machine: 2 units > Model: LID-30 > Features: high-precisi on automatic cutting and punching








Key Process - Welding Workshop



Fully automatic, 360 degree rotating welding line features: Welding accu racy: Welding displacement less tha n 1.5 mm, welding flip angle less tha n 0.1 degrees. Welding software: Ou r self-developed welding control sof tware v1.3 version can store up to 1 28 welding programs. Scan the prod uct code to initiate the welding prog ram, automatically switch between d ual platforms, seamlessly connect, a nd achieve uninterrupted welding. Welding dimensions: Product height 2.8 meters, width 1.5 meters. Weldi ng capacity: 11 fully automatic weldi ng robots and 47 welders. Monthly output of 20000 to 25000 cabinets.

Key Process - Polishing Workshop

- ◆Automatic polishing machine: 2 units, equipment can be increased according to product demand.
 ◆Manual polishing stations: 15, with manpower allocated according to the product structure.





Key Process - Metal Surface Treatment (Fully Automated)

Surface treatment line 1 (parts category)













Surface treatment 2-wire (cabinet

- Full-process foolproofing: Unmanned operation, the sy stem automatically performs surface treatment according to predefined process paths based on different materials, eliminating quality risks caused by human errors.
 Continuous monitoring: The system continuously monitors the pH level of the solution and automatically initiates the addition of the solution based on the monitoring results.
 Monthly capacity: Over 20,000 large cabinets • Full-process foolproofing:

Key process - Metal parts electroplating worksh op (automated assembly line)

Central Conve yor Platform



ng, automatic production line, tunnel oven, and packaging into a whole assembly | nitoring and control, ine to reduce the intermediate loa ding and unloading process and d

tin-plating

Remote con trol platform



Enables remote mo and schedules realtime production

tin-plating


rocedure.

Pre processing p

With a total length of 35 meters, it can simultane ously address each issue point of various alumin



tin-plating



Copper plating pr oduction process



Set up 13 copper plating tanks to si multaneously electroplate 65 units o f products. Each set of 5 units is equ pped with an independent 1500A 48 Fully automatic conver V communication rectifier.

X-ray thickness measu rement equipment



Fischer film thickness gauge imported fro m Germany

Tin plating productio n process



Use tin plating with methyl s Ifonic acid, re placing the pr evious sulfuric acid-based pla ting process.

sion vehicle




Perfectly connect three fully autom ated production lines into an auto mated production platform

Key process - Spray painting workshop (3 main lines+1 auxiliary line/small batch)

Reciprocating machine (auto

tin-plating









Characteristics of Spray Line:

- Characteristics of Spray Line:
 Characteristics of Spray Line: The system monitors the furnace temperature in real-time, and when the oven temperature does not meet the estandard The system monitors the furnace temperature in real-time, and when the oven temperature does not meet the standard. Automatic spraying: Reciprocating machine automatic spraying ensures uniform thickness and aesthetic appearance of the coating.
 Equipment resources: 3 main lines+1 auxiliary line, which can simultaneously meet the needs of different colors:

- ors;

 Daily production capacity;
 15,000 to 20,000 square meter s per day

Automatic Line 3

Key Process - Product Assembly Workshop



Large cabinet as



Small chassis wiring



Small cabinet with assembly line





IPX6 Spray Water Testing System



High voltage prod

Key process - outdoor cabinet waterproof testing assembly line ■Pipeline standard: IPX1-IPX5 waterproof rating, which can be adjust ed and matched according to product requirements.



+86 15817363697



lubenzhi@szdxzh.com



power-cabinets.com

Green Base Industrial Park, Longtian Street, Pingshan District, Shenzhen