WPS30000-150/150 Outdoor Power Cabinet – High-Capacity UPS for Telecom & Data Systems

Basic Information

Place of Origin: CHINA
Brand Name: Daxin
Certification: /

Model Number: ODC-705835CF2P-001

• Minimum Order Quantity: 1 Set

Packaging Details: Woodcase/ Paper box

• Delivery Time: 25-35 days

• Payment Terms: T/T

• Supply Ability: 8000pcs/month



Product Specification

Install Method: Pole/Wall Mount

Material: Galvanized Steel/ Stainless Steel

Customized Service: YesUPS Capacity: 150A

Cooling System: Dual Air Ducts + Fan Cooling

• Highlight: High Capacity Outdoor Power Cabinet,

Data Systems Outdoor Power Cabinet, Telecom Outdoor Power Cabinet



More Images



Product Description

WPS30000-150/150 Outdoor Power Cabinet - High-Capacity UPS for Telecom & Data Systems

Product Overview

The WPS30000-150/150 Outdoor Power Cabinet is a 150A wall-mounted UPS designed for telecom, data communication, and satellite systems. It integrates AC/DC power distribution, temperature control, battery management, and remote monitoring in a rugged IP55-rated outdoor cabinet, supporting wall-mounting, floor-standing, and pole-mounted installations.

Key Features

Max 150A capacity with -54V DC output

Integrated battery management (low-voltage protection, load shedding, temperature compensation)

Remote monitoring via RS232/RS485 & dry contacts

Dual AC/DC lightning protection (C-grade: 20-40kA)

Wide input voltage range (90-300V AC)

High efficiency (up to 95%) with hot-swappable rectifier modules

IP55 protection with forced-air cooling & built-in thermal control

Supports LiFePO4 (50Ah) or lead-acid (4x38Ah) batteries

Technical Specifications

1. General Structure

Component	Configuration	Details
Dimensions (H×W×D)	700×580×350mm	Wall/floor/pole-mount
Cooling System	Dual air ducts + fan cooling	IP55 rated
Battery Support	50Ah LiFePO4 or 4x38Ah lead-acid	Optional

2. Power Distribution & Protection

Unit	Specification
AC Input	63A/2P (Icu≥6kA, Ics≥6kA)
DC Output	150A (adjustable: -42V to -58V)
Lightning Protection	AC: 20-40kA / DC: 10-20kA
Load Shedding	Primary (63A/1P) & Secondary (20A/1P)

3. Electrical Performance

Parameter	Value
Input Voltage	90-300V AC (176-300V full load)
Output Voltage	-54V DC (±1% regulation)
Efficiency	≥95% (220V AC)
Noise Level	≤55dB

4. Environmental Compliance

Condition	Operating Range
Temperature	-40°C to +45°C (full load at -40°C)
Humidity	5-90% RH (non-condensing)
Altitude	≤4000m (derating above 2000m)

Why Choose This Outdoor Power Cabinet?

- ✓ Reliable UPS for Harsh Environments Operates in extreme temperatures (-40°C to +45°C)
- ✓ Smart Battery Management Auto voltage compensation, capacity calculation, and load shedding
- ✓ Flexible Monitoring Supports remote control via RS485/dry contacts
- ✓ High Safety Standards Meets YD/T1058-2000, IEC61000-4-5 (surge protection), and EN55022 (EMC)

Ideal for:

Telecom base stations Satellite & data communication hubs Outdoor power backup systems

Upgrade to the WPS30000-150/150 Outdoor Power Cabinet for unmatched reliability in critical power applications.

Product Details:







Shenzhen Daxin Intelligent Equipment Technology Co., Ltd Shenzhen Daxin Intelligent Equipment Technology Co., Ltd

+86 15817363697

lubenzhi@szdxzh.com

power-cabinets.com

Green Base Industrial Park, Longtian Street, Pingshan District, Shenzhen